# **Ubuntu Server 22.04**

Version:	1.0.0
Created by:	cloudimg

#### **Table of Contents**

1.) Overview	1
· 2.) Access & Security	
3.) System Requirements	
4.) Connecting to the Instance	
5.) On Startup	
6.) Filesystem Configuration	
7.) Server Components	
8.) Scripts and Log Files	4
9.) Using System Components	4

# 1.) Overview

This document is provided as a user guide for the Ubuntu Server 22.04 product offering on the AWS Marketplace. Please reach out to <a href="mailto:support@cloudimg.co.uk">support@cloudimg.co.uk</a> if any issues are encountered following this user guide for the chosen product offering.

# 2.) Access & Security



Please update the security group of the target instance to allow the below ports and protocols for access and connectivity.

Protocol	Туре	Port	Description
SSH	TCP	22	SSH connectivity

### 3.) System Requirements

The minimum system requirements for the chosen product offering can be found below

Minimum CPU	Minimum RAM	Required Disk Space		
1	256 MB	20 GB		

### 4.) Connecting to the Instance

Once launched in the Amazon EC2 Service, please connect to the instance via an SSH client using the **ec2-user** with the key pair associated at launch. Once connected as the **ec2-user** user, you will be able to sudo to the **root** user by issuing the below command.

Switch to the root user.

```
sudo su -
```

NOTE: Please allow the EC2 Instance to reach 2/2 successful status checks to ensure you will be able to connect successfully with the ec2-key pair assigned at launch. Upon attempting to SSH to early you may receive errors such as below, this is expected with an early SSH connection. Allow the EC2 instance to reach 2/2 status checks and you will be able successfully connect with the ec2-key pair assigned at launch as the ec2-user.



#### Example errors you may receive with an early SSH connection.

Permission denied (publickey,gssapi-keyex,gssapi-with-mic).
ec2-user@your-instance-ip's password:



#### 5.) On Startup

An OS package update script has been configured to run on boot to ensure the image is fully up to date at first use. You can disable this feature by removing the script from /stage/scripts/ and deleting the entry in crontab for the root user.

Disable the OS update script from running on reboot

```
rm -f /stage/scripts/initial_boot_update.sh
crontab -e
#DELETE THE BELOW LINE. SAVE AND EXIT THE FILE.
@reboot /stage/scripts/initial_boot_update.sh
```

### 6.) Filesystem Configuration

Please see below for a screenshot of the server disk configuration and specific mount point mappings for software locations.

```
Filesystem Size Used Avail Use% Mounted on tmpfs 95M 816K 94M 1% /run /dev/nvme0n1p3 38G 5.7G 30G 17% / tmpfs 472M 0 472M 0% /dev/shm tmpfs 5.0M 0 5.0M 0% /run/lock /dev/nvme0n1p2 2.0G 186M 1.7G 11% /boot tmpfs 95M 4.0K 95M 1% /run/user/1002
```

Mount Point	Description	
/boot	Operating System Kernel files	

## 7.) Server Components

Please see below for a list of installed server components and their respective installation paths. The below versions are subject to change on initial boot based on the initial\_boot\_update.sh script finding new versions of the software in the systems package repositories.



Component	Version	Software Home	
AWS CLI	2.7.7	/usr/local/aws-cli	
AWS CloudWatch Agent	1.247352.0b251908	/opt/aws/amazon-cloudwatch-agent	
AWS Systems Manager Agent	3.1.1476.0	/usr/bin/amazon-ssm-agent	
Cloud-Init	22.2	/etc/cloud	

### 8.) Scripts and Log Files

The below table provides a breakdown of any scripts & log files created to enhance the useability of the chosen offering.

Script/Log	Path	Description	
Initial_boot_update.sh	/stage/scripts	Update the Operating System with the	
		latest updates available.	
Initial_boot_update.log	/stage/scripts	Provides output for initial_boot_update.sh	

### 9.) Using System Components

Instructions can be found below for using each component of the server build mentioned in section 7 of this user guide document.

#### **AWS CLI**

Using AWS CLI - as any OS user.

awshelp			

#### **AWS CloudWatch Agent**

On first use run the below command as the **root** user to configure the AWS CloudWatch Agent for your needs.

/opt/aws/amazon-cloudwatch-agent/bin/amazon-cloudwatch-agent-config-wizard



Once configured, you will be able to start the AWS CloudWatch Agent via the below command as the **root** user

```
/opt/aws/amazon-cloudwatch-agent/bin/amazon-cloudwatch-agent-ctl -a fetch-config -m ec2 -s -c file:/opt/aws/amazon-cloudwatch-agent/bin/config.json
```

#### Check status of the AWS CloudWatch Agent

```
/opt/aws/amazon-cloudwatch-agent/bin/amazon-cloudwatch-agent-ctl -m ec2 -a status
```

#### **EXAMPLE EXPECTED OUTPUT (This may differ based on your configured setup)**

```
"status": "running",
   "starttime": "2022-06-05T12:10:13+0000",
   "configstatus": "configured",
   "cwoc_status": "stopped",
   "cwoc_starttime": "",
   "cwoc_configstatus": "not configured",
   "version": "1.247350.0b251814"
}
```

#### **AWS Systems Manager**

Check the status of the AWS Systems Manager Agent as the **root** user.

```
systemctl status amazon-ssm-agent
```

#### **Cloud-Init**

Edit the /etc/cloud/cloud.cfg file to reflect your desired configuration. A link to the cloud-init official documentation can be found below for referencing best practise for your use case.

https://cloudinit.readthedocs.io/en/latest/topics/datasources/ec2.html



vi /etc/cloud/cloud.cfg



